

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**DECORATIVE VALVED TRACHEOSTOMY DEVICE*****Field of the Invention***

The invention pertains to tracheostomy tubes, and in particular with the improvement of the aesthetics of such tubes and their accessories.

***Related Art Devices***

Tracheostomy tubes are inserted in the windpipe of the patient to permit breathing wherein the normal esophagus and windpipe have been damaged or diseased. Tracheostomy tubes are inserted in the neck of the wearer and include an internal portion which extends into the windpipe, and the outer end of the tracheostomy tube is provided with a flange and a support plate located exteriorly of the patient having an opening therein communicating with the tube through which breathing air is inhaled. In many patients, speaking is possible by closing the outer end of the tube after inhalation whereby air may be forced through the vocal cords. The control of air through the tracheostomy tube is often by placing the finger over the opening in the tube support plate during speaking, and releasing the finger valve when inhaling air. Such motions become second nature to the wearer, but are often disconcerting to those the tracheostomy patient is speaking. Tracheostomy patients become objects of curiosity to many, particularly children who do not understand why a person would have a hole in their neck, and tracheostomy patients often become self-conscious of their situation and condition with attendant mental discomfort.

Some tracheostomy tubes have unidirectional valves at their outer ends wherein the valve will permit air to enter the tube, but prevent exhaling through the tube. The use of the one-way valve eliminates the need for the patient to place a finger over the tube opening, but

the valve, often of the check valve ball type, requires that the valve structure extend significantly from the tracheostomy tube flange and support plate and significant structure appears at the patient's neck which is, also, of an unusual appearance and the patient is self-conscious of the apparatus. Such speaking valve tracheostomy tubes are offered by Pilling Weck Surgical Company Models 51-8025A and 51-8575, and related model numbers. Accordingly, a tracheostomy tube with a valve has not heretofore been available which is of an attractive appearance and is not a matter of curiosity to the uninitiated.

### *Object of the Invention*

An object of the invention is to provide a tracheostomy tube apparatus which is capable of being used with conventional tracheostomy tubes wherein a valve may be associated with the tube outer end and the valve structure is of a low profile and appears as an item of attractive neck jewelry which is aesthetically pleasing and unobtrusive.

Another object of the invention is to provide a tracheostomy tube device of the valved type which appears as an item of jewelry, rather than a medical device, and where the device may be easily cleaned and maintained.

Yet another object of the invention is to provide a tracheostomy tube of the valved type having a decorative cap wherein the device will have a jewelry appearance, and by substituting one cap for another, the appearance of the valved device may be readily varied for fashion and color matching purposes.

Another object of the invention is to provide a tracheostomy tube of relatively simple construction wherein a low profile valve housing is associated with the outer end of the tube and the valve housing is located within a decorative cap, while an attractive jewelry-type

necklace may be associated with the tube support plate so that the entire device has the appearance of neck jewelry, rather than a medical apparatus.

A further object of the invention is to provide a valved tracheostomy tube apparatus having the appearance of neck jewelry that is readily cleaned, easily maintained by the patient and may be readily varied in appearance in accordance with the costume jewelry aspect of the invention and requires no special skills for the minor modification required to change appearance.

### *Summary of the Invention*

The valved tracheostomy tube valve of the invention may be employed with a conventional tracheostomy tube having a flange and/or a support plate end to which attachment devices may be affixed, as is commonly known. The valve housing of the apparatus may be attached to many conventional tracheostomy tube support plates and flanges, and may be readily adapted to various attachment devices used by various manufacturers of tracheostomy tubes. In the disclosed embodiment, by way of disclosure, the valve structure is attached to the tracheostomy tube flange by a ball bayonet connection.

The valve housing connected to the tracheostomy tube flange a bayonet connection is preferably formed of an acceptable food grade plastic material and includes a stem extending into the tracheostomy tube constituting an outlet port for the valve housing. Preferably, although not necessarily, the valve housing is of a circular configuration having a decorative cap affixed thereto which maintains the assembly of the valve components, and also provides a decorative aspect to the valve housing making it appear as neck jewelry.

The valve housing includes inlet ports whereby atmospheric air may be drawn into the

valve housing. The inlet air is in communication with a relatively flat diaphragm-type valve having a flexible flap and a hinge whereby the edgewise profile of the flap is very small permitting the profile of the valve housing to be of a small size, such as 3/8". Preferably, the length of the valve extending beyond the tube support plate is approximately the dimension of the tube opening. An outlet port or passage is defined in the valve housing communicating with the valve structure and the housing stem and tracheostomy tube whereby air may pass through the valve housing into the tube, but the valve automatically closes and prevents air from flowing from the tube through the valve housing. In this way, a uni-directional air flow from the atmosphere to the tube is provided, eliminating the necessity of the patient to use their finger as a valve.

The valve components, such as the inlet valve plate and diaphragm valve are held in place by a cap threaded upon the exterior of the valve housing. The cap includes a base having a front side which is apparent to the observer, and its front side may be decorated with engravings, semi- or precious stones, or other decorative items. The cap threads upon the valve housing and may be readily attached or removed from the valve housing for decorative changing purposes, or to permit cleaning of the valve housing components.

Preferably, a flexible necklace, such as a gold or silver chain, circumscribes the wearer's neck having ends attached to the tracheostomy tube support plate. The use of the flexible necklace, which is common neck jewelry, further lends to the apparatus a decorative appearance and yet helps maintain the tube in position, and is a substitute for the medical type neck devices commonly used with tracheostomy tubes.

The entire assembly of the low profile valve housing with the decorative cap and the necklace renders a previously objectionable medical device to a type of neck jewelry which is

unobtrusive and attractive in appearance, and the invention changes the tracheostomy patient from an object of curiosity to a normal person.

***Brief Description of the Drawings***

The aforementioned objects and advantages of the invention will be appreciated from the following description and drawings wherein:

Fig. 1 is a partial front view of a tracheostomy tube patient having a necklace in accord with the invention attached to a tracheostomy tube support plate, and before the valve housing has been attached to the tube flange,

Fig. 2 is a view similar to Fig. 1 after the valve housing has been attached to the tube flange and is positioned over the support plate,

Fig. 3 is a perspective view of a conventional tracheostomy tube assembly prior to a valve housing being placed thereon,

Fig. 4 is a diametrical sectional view of a valve housing in accord with the invention,

Fig. 5 is a rear view of the valve housing as taken from the top of Fig. 4,

Fig. 6 is a front view of the valve housing upon the removal of the cap illustrating the air inlet ports and the valve cover,

Fig. 7 is a front view of the valve housing upon removal of the valve cover illustrating the flexible valve structure,

Fig. 8 is a front view of the valve housing upon the removal of the flexible valve, and

Fig. 9 is an elevational sectional view of the valve housing with the cap and interior components removed.

*Description of the Preferred Embodiment*

With reference to the drawings, the wearer of the tracheostomy device is shown at **10**, and, of course, the wearer includes a neck **12**. A typical tracheostomy tube is shown in Fig. 3 wherein the tube **14** will fit into the patient's airpipe and the tube **14** may be located within another tube which has been affixed within the patient. The tube **14** includes an outer end which is flanged at **18** and a support plate **16** is located at the tube outer end below the flange **18**. The flange **18** includes the end opening **20** in communication with the tube **14** and a male bayonet ball connection **22** is located upon the flange **18** for attachment of the valve housing thereto, as later described. The bayonet ball **22** includes a short stem supporting a spherical ball for fitting in the female ball bayonet slot in the valve housing, as described below.

The support plate **16** includes ends, and attachment holes **24** are defined adjacent the ends of the support plate **16** for receiving the necklace clasp as later described. The structure shown in Fig. 3 is relatively typical of tracheostomy tube constructions and the invention may be retrofitted to conventional tubes.

The valve housing **26** is preferably formed of a food quality synthetic plastic material, and the valve housing **26** is of a generally circular configuration as will be appreciated from Figs. 5-8. The valve housing includes a circular central stem **28** which fits within the tracheostomy tube opening **20**, and the valve housing **26** includes the female bayonet keyhole slot **30**, Fig. 5, for receiving the bayonet ball **22** wherein a slight rotation of the valve housing relative to the flange **18** will connect the valve housing in place upon the flange **18** and the support plate **16**.

The generally circular valve housing **26** is provided with an outer periphery upon

which threads **32** are defined, and the valve housing includes an outer face **34** which bears against the cap base as later described. Within the outer face **34**, a circular opening **36** is defined in the valve housing **26**, and as will be appreciated from Figs. 6-9, the circular opening **36** is off center with respect to the stem **28** and housing **26**. The stem **28** is coaxially centered upon the valve housing **26** and is coaxial with the threads **32**. The reason the circular opening **36** is offset with respect to the stem **28** is to provide clearance for the band keyhole slot **30** and yet a maximum diameter valve may be employed within a relatively confined configuration.

The circular opening **36** includes a circular shoulder **38** against which the valve engages, as later described, and the outlet port **40** communicates with the interior of the stem **28**, Fig 9, whereby air passing through the valve housing will unidirectionally enter the stem **28** from the valve.

Air into the valve housing **26** is through the washer-like valve cover **42**. The valve cover **42** has short posts **44** which space the body of the valve cover from the cap, later described, to provide air passage **46** in the valve cover which is in communication with the central opening **48**. The valve cover **42** closely fits within the valve housing circular opening **36**, Figs. 4 and 6.

Air inlet port passages **50** are defined within the valve housing intersecting the rear of the valve housing as will be appreciated from Fig. 5. The inlet ports **50** are defined in the periphery of the valve housing **26**, and include radial channels **52** in face **34**, Fig. 9, which communicate with the passage **46** of the valve cover **42**. In this manner, the inlet air passes into the valve housing through its rear through the inlet ports **50** and into the valve cover **42**.



Air entering the valve cover flows through the central opening 48 which communicates with the center of the flexible valve 52.

The valve 52 is best shown in Fig. 7 and is formed of a flexible resilient material such as of rubber, synthetic plastic, or the like which is capable of limited flexing and is resilient enough to return to its original flat configuration when not being deformed by air flowing into the valve housing. The valve 52 includes a peripheral edge portion 54, Fig. 7, which seals against shoulder 38, and a central flat portion 56 is hinged to the edge 54 at 58. As will be appreciated from Figs. 4 and 7, the flat portion 56 is of a greater diameter than the valve cover central opening 48, and air passing through the opening 48 may pass into the outlet port 40, but the valve flap 56 seals and closes against the smooth back of the valve cover 42 which acts as a valve seat during the exhaling of the wearer 10.

A cap 60 threads upon the valve housing 26. The cap 60 illustrated is plastic, but may be made of metal, or plated plastic or other material. The cap 60 includes a central base 62 and a peripheral axially extending lip 64 having internal threads 66 defined thereon. In this manner, the cap 60 may be easily threaded upon the exterior threads 32 of the valve housing 26. The cap 60 is threaded upon the valve housing 26 until the interior surface of the base 60 engages the front face 34 of the valve housing. Of course, the presence of the inlet ports 50 permit air to enter the rear of the valve housing, pass along the base of the cap in passages 52 and 46 into the valve cover 42.

The cap base 62 includes an exterior front side 68 which is visibly apparent. The front side 68 may include engravings or other decorative features, such as semi-precious or precious stones, or any variety of decorative material. Of course, the cap 60 may be gold or



10